

SPECIFICATION

COMMERCIALY AVAILABLE

CERAMIC BAND PASS
PART NUMBER: CF-24301005A
RoHS

REVISED 07/12/2018: UPDATED FORMATTING

ISSUED / REVISION	ENGINEER APPROVED	DOCUMENT CHECKED	DRAFTSMAN	DOCUMENT CHECKED
6/9/15 ^(kn)				
07/12/18 ^(TF)				

FILTRONETICS Inc

1. APPLICATION

THIS SPECIFICATION APPLIES TO A BAND PASS FILTER, USING DIELECTRIC RESONATORS.


2. PART NUMBER: CF-24301005A

3. PACKAGING: PLASTIC TRAY


4. SPECIFICATIONS:

Parameter	Unit	Specification
Center Frequency	MHz	2430
1.0 dB Bandwidth	MHz	$F_c \pm 50$ (2380 ~ 2480MHz)
Insertion Loss at F_c	dB	3.0 max.
Return Loss in BW	SWR	1.75:1 Max
Attenuation (Absolute Value)	dB	40 min. @ DC ~ 2280MHz
		12 min. @ 2520 ~ 3200MHz
Input Power	Watt	1 max.
IN/OUT Impedance	Ω	50
Operating Temp. Range	$^{\circ}\text{C}$	-35 ~ +85


S21 LOG MAG NETWORK ANALYZER



S11 SWR NETWORK ANALYZER



4. Dimensions:




MATERIAL SPECIFICATION	
2.	PCB
1)	MATERIAL: FR4
2)	TERMINALS: Au PLATED
3.	METAL CASE
1)	MATERIAL: Sn OR Ni PLATED
4.	RESONATOR
1)	COATING MATERIAL: Ag
2)	DIMENSION: 3.0MM x 3.0MM

MARKING	
Part No	Filtronetics, Inc.
Date Code	YY: YEAR
WW: WEEK	
UNIT:MM	
TOLERANCE: +/-0.5MM	
IN/OUT LAND: +/-0.3MM	

● **CAUTIONS:**

1. When handling products, be careful not to damage the outer-electrode.
2. When handling products be careful not to touch the outer-electrode with bare hands or solderability is reduced.
3. Do not apply excessive pressure or shock to product in handling or in transportation or damage to the ceramic filters may result.
4. If boards are cleaned after installation, units must be completely dried.

5. GRAPHS:




6. DEFINITIONS:

TERMS	DESCRIPTION	SPECIFICATION
Center Frequency	The midpoint of through band pass filter pass band, normally expressed as the arithmetic mean of the -3db point. Also called fo.	3. SPECIFICATION
Pass Band Width	The width of the pass band of a filter referenced to the minimum insertion loss point in the pass band. The pass band of a filter is stated as -1.0dB bandwidth.	
Insertion Loss	The loss of the filter, in db, measured at center frequency relative to a through line (0 dB).	
Attenuation	Reduction of RF power through a filter measured in dB, at desired band and referenced to 0 dB. (Filter to be removed from circuit)	
Pass Band Ripple	Variations in loss in the pass band of the filter, superimposed upon the fundamental shape of the pass band.	
V.S.W.R in Pass Band	The ratio of the maximum value of a standing wave to its minimum value, related to the return loss in pass band.	

7. RELIABILITY TEST AND CONDITIONS:

ITEM	TEST CONDITIONS	REQUIREMENTS
Resistance to solder heat	Preheat temperature : 120 to 150°C Preheat time: 1 to 1.5 min Solder temperature: 260 +/- 10°C Dipping time: 10 +/- 0.5 sec	No damage such as cracks should be caused in chip element.
Solderability	Preheat temperature: 120 to 150°C Preheat time: 1 to 1.5 min Solder temperature: 235 +/- 5°C Dipping time: 5 +/- 1 sec	More than 80% of the terminal electrode shall be covered with new solder
Heat resistance (High-temperature Load)	Temperature: 85 +/- 2°C Applied voltage: Rated voltage Applied current: Rated current Recovery: 1 to 2hrs of recovery under the standard condition after the removal from test chamber.	No mechanical damage. After test, the device shall satisfy the specification in section 3.
Thermal shock (Temperature cycle)	Conditions for 1 cycle Step 1: + 85°C 15 min Step 2 : - 30°C 15 min Number of cycle: 10	No mechanical damage. After test, the device shall satisfy the specification in section 3.
Vibration	Frequency: 10 ~ 50 Hz Amplitude: 1.52mm (0.060 inches) Direction: X, Y and Z Time: each 30 min for all directions	No mechanical damage. After test, the device shall satisfy the specification in section 3.

8. REFLOW SOLDERING STANDARD CONDITIONS FOR RoHS



- Measuring point of temperature in-out terminals of the device.
- Reflow Soldering
- Both convection and infrared rays
- Hot air
- Hot plates
- Solder Cream: Sn96.5/Ag3.5