

SPECIFICATION

COMMERCIALLY AVAILABLE

CERAMIC BAND PASS
PART NUMBER: CF-56008005
RoHS

11/20/13 Corrected Reflow profile

ISSUED / REVISION	ENGINEER APPROVED	DOCUMENT CHECKED	DRAFTSMAN	DOCUMENT CHECKED
3/18/2010 DS	3/24/2010 SRJ	3/25/2010 BF		
8/17/11kn				
11/20/13 ^(kn)	12/05/2013 TFG		12/05/2013 GL	

FILTRONETICS Inc

1. APPLICATION

THIS SPECIFICATION APPLIES TO BAND PASS FILTER, USING DIELECTRIC RESONATORS.


2. PART NUMBER: CF56008005

3. SPECIFICATIONS

Center Frequency (Fo)	5600 MHz
Poles	5
-1dB Band Width(BW)	800 MHz
Insertion Loss @ F0	2.0 dB max
Ripple in BW	1.0 dB max
Return Loss BW	15 dB min
Rejection	40 dBc min @ 2200 MHz 40 dBc min @ 7400 MHz
In/Out Impedance	50 Ω
Temperature Range	-40 ~ +85°C
Power Handling	1 watt
This product is RoHS compliant.	

4. DIMENSIONS

Marking:
CF-56008005
YY/MM



RESONATOR	MATERIAL	PLATE
	CERAMIC (ϵ_r : 90,38,20,8) (Barium, Titanium, Samarium, Manganese, Oxide)	Ag (RF-Dipping Paste)
C-COUPLER	CERAMIC (ϵ_r : 4, 9, 21, 38) (Barium, Titanium, Samarium, Manganese, Oxide) Alumina substrates (AL ₂ O ₃)	Ag (RF-Printing Paste)
C- COUPLER BLOCK	BsT (Brass (Cu, Zn))	Sn
CASE	BsT (Brass (Cu, Zn))	Sn
P.C.B	FR-4 (COPPER, GLASS FABRIC, EPOXY RESIN)	Au
SOLDER	Sn 96.5% / Ag 3.0% / Cu 0.5%	


5. DEFINITIONS:

TERMS	DESCRIPTION	SPECIFICATION
Center Frequency	The midpoint of through band pass filter pass band, normally expressed as the arithmetic mean of the -3dB point. Also called Fo.	3. SPECIFICATION
Pass Band Width	The width of the pass band of a filter referenced to the minimum insertion loss point in the pass band. The pass band of a filter is stated as -1.0dB bandwidth.	
Insertion Loss	The loss of the filter, in dB, measured at center frequency relative to a through line (0 dB).	
Attenuation	Reduction of RF power through a filter measured in dB, at desired band and referenced to 0 dB. (Filter to be removed from circuit)	
Pass Band Ripple	Variations in loss in the pass band of the filter, superimposed upon the fundamental shape of the pass band.	
V.S.W.R in Pass Band	The ratio of the maximum value of a standing wave to its minimum value, related to the return loss in pass band.	

6. RELIABILITY TEST AND CONDITIONS:

ITEM	TEST CONDITIONS	REQUIREMENTS
Resistance to solder heat	Preheat temperature : 120 to 150°C Preheat time: 1 to 1.5 min Solder temperature: 260 +/- 10°C Dipping time: 10 +/- 0.5 sec	No damage such as cracks should be caused in chip element.
Solderability	Preheat temperature: 120 to 150°C Preheat time: 1 to 1.5 min Solder temperature: 235 +/- 5°C Dipping time: 5 +/- 1 sec	More than 80% of the terminal electrode shall be covered with new solder
Heat resistance (High-temperature Load)	Temperature: 85 +/- 2°C Applied voltage: Rated voltage Applied current: Rated current Recovery: 1 to 2hrs of recovery under the standard condition after the removal from test chamber.	No mechanical damage. After test, the device shall satisfy the specification in section 3.
Thermal shock (Temperature cycle)	Conditions for 1 cycle Step 1: + 85°C 15 min Step 2 : - 30°C 15 min Number of cycle: 10	No mechanical damage. After test, the device shall satisfy the specification in section 3.
Humidity Resistance	Temperature: 40 +/- 2°C Humidity: 90 to 95% RH Duration: 96 +/- 5 hrs Recovery: 1 to 2hrs of recovery under the standard condition after the removal from test chamber.	No mechanical damage. After test, the device shall satisfy the specification in section 3.
Vibration	Frequency: 10 ~ 50 Hz Amplitude: 1.52mm (0.060 inches) Direction: X, Y and Z Time: each 30 min for all directions	No mechanical damage. After test, the device shall satisfy the specification in section 3.

7. REFLOW SOLDERING STANDARD CONDITIONS FOR RoHS



- Measuring point of temperature in-out terminals of the device.
- Reflow Soldering
- Both convection and infrared rays
- Hot air
- Hot plates
- Solder Cream: Sn96.5/Ag3.5