

SPECIFICATION

COMMERCIALLY AVAILABLE

CERAMIC MONOBLOCK
PART NUMBER: CFM-038301010
RoHS

Also available with SMA, see FNP-1460


ISSUED / REVISION	ENGINEER APPROVED	DOCUMENT CHECKED	DRAFTSMAN	DOCUMENT CHECKED
09/26/2018 ^(AM)				
FILTRONETICS Inc				

1. PART NUMBER: CFM-038301010

2. SPECIFICATIONS:

Parameter	Unit	Specification
Center Frequency	MHz	382.5
Bandwidth	MHz	$F_c \pm 5$ (377.5 ~ 387.5MHz)
Insertion Loss in $F_c \pm 2.5$ MHz	dB	2.5 max.
Ripple in $F_c \pm 2.5$ MHz	dB	1.0 max.
Return Loss in $F_c \pm 2.5$ MHz	dB	15.0 min.
Attenuation	dB	40.0 min. @ DC ~ 372.5MHz
		40.0 min. @ 392.5 ~ 500MHz
Input Power	Watt	10 CW max.
IN/OUT Impedance	Ω	50
Operating Temp. Range	$^{\circ}\text{C}$	-20 ~ +55

3. DIMENSIONS:



NOTES:


1. Surface mount package
2. Dimensions in millimeters
3. Max reflow temperature 260°C for 10 sec
4. If boards are cleaned after installation units must be completely dried
5. Tolerance unless specified: ± 0.3
6. **** _> Date code (YYWW)

4. SIMULATION:

3/29/2017 10:45:18 AM
1311.6010K64-101529-01

Trc1 — S11 dB Mag 5 dB/ Ref 0 dB Cal int Trc2 — S21 dB Mag 10 dB/ Ref 0 dB Cal int
Trc3 — S22 dB Mag 5 dB/ Ref 0 dB Cal int

1




5. DEFINITIONS:

TERMS	DESCRIPTION	SPECIFICATION
Center Frequency	The midpoint of through band pass filter pass band, normally expressed as the arithmetic mean of the -3db point. Also called f_0 .	3. SPECIFICATION
Pass Band Width	The width of the pass band of a filter referenced to the minimum insertion loss point in the pass band. The pass band of a filter is stated as -1.0dB bandwidth.	
Insertion Loss	The loss of the filter, in db, measured at center frequency relative to a through line (0 dB).	
Attenuation	Reduction of RF power through a filter measured in dB, at desired band and referenced to 0 dB. (Filter to be removed from circuit)	
Pass Band Ripple	Variations in loss in the pass band of the filter, superimposed upon the fundamental shape of the pass band.	
V.S.W.R in Pass Band	The ratio of the maximum value of a standing wave to its minimum value, related to the return loss in pass band.	

6. RELIABILITY TEST AND CONDITIONS:

ITEM	TEST CONDITIONS	REQUIREMENTS
Resistance to solder heat	Preheat temperature : 120 to 150°C Preheat time: 1 to 1.5 min Solder temperature: 260 +/- 10°C Dipping time: 10 +/- 0.5 sec	No damage such as cracks should be caused in chip element.
Solderability	Preheat temperature: 120 to 150°C Preheat time: 1 to 1.5 min Solder temperature: 235 +/- 5°C Dipping time: 5 +/- 1 sec	More than 80% of the terminal electrode shall be covered with new solder
Heat resistance (High-temperature Load)	Temperature: 85 +/- 2°C Applied voltage: Rated voltage Applied current: Rated current Recovery: 1 to 2hrs of recovery under the standard condition after the removal from test chamber.	No mechanical damage. After test, the device shall satisfy the specification in section 3.
Thermal shock (Temperature cycle)	Conditions for 1 cycle Step 1: + 85°C 15 min Step 2 : - 30°C 15 min Number of cycle: 10	No mechanical damage. After test, the device shall satisfy the specification in section 3.
Humidity Resistance	Temperature: 40 +/- 2°C Humidity: 90 to 95% RH Duration: 96 +/- 5 hrs Recovery: 1 to 2hrs of recovery under the standard condition after the removal from test chamber.	No mechanical damage. After test, the device shall satisfy the specification in section 3.
Vibration	Frequency: 10 ~ 50 Hz Amplitude: 1.52mm (0.060 inches) Direction: X, Y and Z Time: each 30 min for all directions	No mechanical damage. After test, the device shall satisfy the specification in section 3.

7. REFLOW SOLDERING STANDARD CONDITIONS



- Measuring point of temperature in-out terminals of the device.
- Reflow Soldering
- Both convection and infrared rays
- Hot air
- Hot plates
- Solder Cream: Sn64/Pb36