

# SPECIFICATION

ITEM: DIELECTRIC CERAMIC FILTER  
PART NUMBER: CFM-35620273

ISSUED	CHECKED	CHECKED	CHECKED	APPROVED

**FILTRONETICS Inc**

**1. APPLICATION**

THIS SPECIFICATION APPLIES TO A BAND PASS FILTER USING DIELECTRIC RESONATORS.


**2. PART NUMBER**

PART NO	CFM-35620273
PACKAGING	Tape and Reel


**3. SPECIFICATIONS**

NO	Parameter		Specification
1	Center Frequency (Fo)	a1	3562.5 MHz
2	Pass Bandwidth (BW)	b1	27 MHz (3549 ~ 3576)
3	Insertion Loss in BW	c1	2.5 dB Max
4	Ripple in BW	d1	0.5 dB Max
5	Return Loss in BW	i1	15.0 dB Min
6	Attenuation	DC ~ 2500 MHz	35 dB Min
		At 3065 ~ 3096 MHz	40 dB Min
		At 3309 ~ 3336 MHz	35 dB Min
		At 3428 ~ 3455 MHz	30 dB Min
		At 3449 ~ 3471 MHz	15 dB Min
		At 4000 MHz	35 dB Min
7	Impedance		50 Ohms
8	Power Rating		1 W Max
9	Operating Temperature		-40°C to +85 °C

**S21 LOG MAG NETWORK ANALYZER**




**S11 LOG MAG NETWORK ANALYZER**




1. 4. GRAPHS


S21 & S11 (Insertion Loss, Ripple, Return Loss, Attenuation at 3428, 3455 MHz)




S21 & S11 (Attenuation at 2500, 3065, 3096, 3309, 3336 MHz)



S21 & S11 (Attenuation at 3449, 3471, 4000 MHz)



5. DIMENSIONS



※ MATERIAL SPECIFICATION

1. RESONATOR
  - 1) COATING MATERIAL: Ag
2. ROHS Compliant

※ MARKING

CFM-35620273  
Date Code

UNIT: MM  
TOLERANCE: +/-0.3MM

- CAUTIONS:
  1. When handling products, be careful not to damage the outer-electrode.
  2. When handling products be careful not to touch the outer-electrode with bare hands or solderability is reduced.
  3. Do not apply excessive pressure or shock to product in handling or in transportation or damage to the ceramic filters may result.


**6. DEFINITIONS**

TERMS	DESCRIPTION	SPECIFICATION
Center Frequency	The midpoint of through band pass filter pass band, normally expressed as the arithmetic mean of the -3db point. Also called $f_0$ .	3. SPECIFICATION
Pass Band Width	The width of the pass band of a filter referenced to the minimum insertion loss point in the pass band. The pass band of a filter is stated as -1.0dB bandwidth.	
Insertion Loss	The loss of the filter, in db, measured at center frequency relative to a through line (0 dB).	
Attenuation	Reduction of RF power through a filter measured in dB, at desired band and referenced to 0 dB. (Filter to be removed from circuit)	
Pass Band Ripple	Variations in loss in the pass band of the filter, superimposed upon the fundamental shape of the pass band.	
V.S.W.R in Pass Band	The ratio of the maximum value of a standing wave to its minimum value, related to the return loss in pass band.	

**7. RELIABILITY TEST AND CONDITIONS**

ITEM	TEST CONDITIONS	REQUIREMENTS
Resistance to solder heat	Preheat temperature : 120 to 150°C Preheat time: 1 to 1.5 min Solder temperature: 260 +/- 10°C Dipping time: 10 +/- 0.5 sec	No damage such as cracks should be caused in chip element.
Solderability	Preheat temperature: 120 to 150°C Preheat time: 1 to 1.5 min Solder temperature: 235 +/- 5°C Dipping time: 5 +/- 1 sec	More than 80% of the terminal electrode shall be covered with new solder
Heat resistance (High-temperature Load)	Temperature: 85 +/- 2°C Applied voltage: Rated voltage Applied current: Rated current Recovery: 1 to 2hrs of recovery under the standard condition after the removal from test chamber.	No mechanical damage. After test, the device shall satisfy the specification in section 3.
Thermal shock (Temperature cycle)	Conditions for 1 cycle Step 1: + 85°C 15 min Step 2 : - 30°C 15 min Number of cycle: 10	No mechanical damage. After test, the device shall satisfy the specification in section 3.
Humidity Resistance	Temperature: 40 +/- 2°C Humidity: 90 to 95% RH Duration: 96 +/- 5 hrs Recovery: 1 to 2hrs of recovery under the standard condition after the removal from test chamber.	No mechanical damage. After test, the device shall satisfy the specification in section 3.
Vibration	Frequency: 10 ~ 50 Hz Amplitude: 1.52 mm ( 0.060 inches) Direction: X, Y and Z Time: each 30 min for all directions	No mechanical damage. After test, the device shall satisfy the specification in section 3.

**8. REFLOW SOLDERING STANDARD CONDITIONS**



- Measuring point of temperature in-out terminals of the device.
- Reflow Soldering
- Both convection and infrared rays
- Hot air
- Solder Cream: Sn96.5/Ag3.5